

DROP-IN ISOLATORS(HIGH POWER)

FREQUENCY (GHz)	MODEL	ISOLATION dB(Min.)	INS. LOSS dB(Max.)	VSWR (Max.)	TEMP (°C)	POWER(WATTs) FWD/REV	DIMENSIONS (INCHES)LxWxT	PACKAGE OUTLINE
0.800-0.824	NI081BT	23	0.25	1.20:1	-30~+85	150/100	1.0x1.25x0.25	B
0.810-0.915	NI086BT	18	0.35	1.25:1	-30~+85	150/100	1.0x1.25x0.25	B
0.824-0.849	NI084BT	23	0.25	1.20:1	-30~+85	150/100	1.0x1.25x0.25	B
0.869-0.894	NI088BT	22	0.25	1.20:1	-30~+85	150/100	1.0x1.25x0.25	B
0.860-0.904	NI089BT	23	0.25	1.20:1	-30~+85	150/100	1.0x1.25x0.25	B
0.880-0.940	NI910BT	21	0.27	1.20:1	-30~+85	150/100	1.0x1.25x0.25	B
0.890-0.915	NI090BT	23	0.25	1.20:1	-30~+85	150/100	1.0x1.25x0.25	B
0.935-0.960	NI094BT	23	0.25	1.20:1	-30~+85	150/100	1.0x1.25x0.25	B
0.890-0.960	NI092BT	21	0.35	1.20:1	-30~+85	150/100	1.0x1.25x0.25	B
0.915-0.964	NI094BT	22	0.30	1.20:1	-30~+85	150/100	1.0x1.25x0.25	B
0.980-1.020	NI099BT	22	0.30	1.20:1	-30~+85	150/100	1.0x1.25x0.25	B
1.000-1.060	NI103BT	22	0.30	1.25:1	-30~+85	150/100	1.0x1.25x0.25	B
1.250-1.350	NI130BT	21	0.30	1.25:1	-30~+85	150/100	1.0x1.25x0.25	B
1.400-1.600	NI150BT	18	0.35	1.25:1	-30~+85	150/100	1.0x1.25x0.25	B
1.410-1.453	NI144BT	23	0.25	1.20:1	-30~+85	150/100	1.0x1.25x0.25	B
1.429-1.501	NI147BT	20	0.25	1.20:1	-30~+85	150/100	1.0x1.25x0.25	B
1.477-1.501	NI149BT	23	0.25	1.20:1	-30~+85	150/100	1.0x1.25x0.25	B
1.500-1.660	NI158BT	18	0.30	1.25:1	-30~+85	150/100	1.0x1.25x0.25	B
1.750-1.780	NI176CT	23	0.25	1.20:1	-30~+85	125/100	0.75x1.0x0.20	C
1.840-1.870	NI185CT	23	0.25	1.20:1	-30~+85	125/100	0.75x1.0x0.20	C
1.805-1.880	NI184CT	21	0.25	1.20:1	-30~+85	125/100	0.75x1.0x0.20	C
1.850-1.910	NI188CT	21	0.25	1.20:1	-30~+85	125/100	0.75x1.0x0.20	C
1.850-1.990	NI192CT	21	0.25	1.20:1	-30~+85	125/100	0.75x1.0x0.20	C
1.800-2.000	NI190CT	20	0.35	1.20:1	-30~+85	125/100	0.75x1.0x0.20	C
1.920-1.980	NI195CT	23	0.25	1.20:1	-30~+85	125/100	0.75x1.0x0.20	C
1.930-1.990	NI196CT	23	0.25	1.20:1	-30~+85	125/100	0.75x1.0x0.20	C
2.110-2.170	NI214CT	23	0.25	1.20:1	-30~+85	125/100	0.75x1.0x0.20	C
2.000-2.200	NI210CT	20	0.35	1.25:1	-30~+85	125/100	0.75x1.0x0.20	C
2.000-2.300	NI215CT	18	0.40	1.25:1	-30~+85	125/100	0.75x1.0x0.20	C
2.300-2.500	NI240CT	20	0.35	1.22:1	-30~+85	125/100	0.75x1.0x0.20	C
2.300-2.700	NI250CT	18	0.35	1.25:1	-30~+85	125/100	0.75x1.0x0.20	C
2.400-2.500	NI245CT	23	0.30	1.2:1	-30~+85	125/100	0.75x1.0x0.20	C
2.630-2.660	NI264CT	23	0.25	1.2:1	-30~+85	125/100	0.75x1.0x0.20	C
2.700-2.900	NI280CT	20	0.35	1.25:1	-30~+85	125/100	0.75x1.0x0.20	C
2.900-3.100	NI300CT	20	0.35	1.25:1	-30~+85	125/100	0.75x1.0x0.20	C
3.100-3.400	NI325CT	20	0.35	1.25:1	-30~+85	125/30	0.75x1.0x0.20	C
3.400-3.700	NI355CT	20	0.35	1.25:1	-30~+85	125/30	0.75x1.0x0.20	C